FIREPLACE, WOOD BURNING STOVE SUPPLEMENT

ATTACH PHOTO COMPLETE IN FULL			
APPLICANT		POLICY/QUOTE NUMBER	
FIREPLACE INSERT COMPLETE QUESTIONS 1-6			FREE STANDING FIREPLACE &/OR STOVE COMPLETE QUESTIONS 1-6
		☐ Free Standing Stove	
Furnace Supplement Other:			
2. IS THIS UNIT A MAJOR HEAT SOURCE FOR THE DWELLING			
☐ Yes ☐ No 3. WERE CHIMNEY AND EQUIPMENT INSTALLED BY CONTRACTOR NAME AND ADDRESS IF OTHER THAN THE HOME BUILDER ☐ Yes ☐ No			
4. CHIMNEY INFORMATION – TYPE OF CHIMNEY Masonry with tile flue liner Prefab'd metal chimney (UL approved)			
☐ Other WHEN WAS CHIMNEY LAST CLEANED HOW OFTEN IS CHIMNEY CLEANED			
WHEN WAS CHIMNET LAST CLEANED	TIOV	OF TEN IS CHIMINET CLEANED	
CLEANED BY WHOM Insured Chimney Sweep* Contractor*			
*NAME AND ADDRESS			
IS MORE THAN ONE UNIT VENTED INTO THE SAME CHIMNEY FLUE			
☐ Yes ☐ No			
THE FOLLOWING QUESTIONS SHOULD BE ANSWERED FOR FREE STANDING FIREPLACES AND/OR STOVES.			
BRAND NAME	YEA	R PURCHASED	
5. DOES YOUR FREE STANDING HEATING UNIT HAVE THE MINIMUM CLEARANCES OF:			
☐ Yes ☐ No 36" between the stove box and any unprotected combustible surface in all directions			
☐ Yes ☐ No 4" between stove and floor			
☐ Yes ☐ No Pad under stove (see diagrams below)			
6. STOVE PIPE INFORMATION – DIAMETER OF PIPE DISTANCE FROM THE NEAREST COMBUSTIBLE SURFACE			
ARE PIPE SECTIONS OR JOINTS FASTENED WITH METAL SCREWS Yes No		DOES THE PIPE PASS THROUGH FLOOR, WALLS OR CEILINGS Yes No	
IF SO, IS IT PROTECTED WITH A			
☐ Ventilated thimble ☐ Fuel connector ☐ Fire stop spacer IS MORE THAN ONE UNIT VENTED INTO THE SAME CHIMNEY			
☐ Yes ☐ No			
DATE / /	INSU	IRED'S SIGNATURE	
Minimum Clearance			
24"Thimble			
8" Pipe			
Damper			
36"			
6"-4" 4" U 18"			
THESE CLEARANCES CAN BE REDUCED IF YOUR FLOOR OR COMBUSTIBLE WALL IS PROTECTED BY BRICKS WITH MORTAR OR BY METAL COVERED ASBESTOS STOVE BOARD. THE PAD UNDER YOUR STOVE SHOULD EXTEND 18" BEYOND THE ASH REMOVAL DOOR OR YOUR STOVE.			